



Quadro K5000 for Mac
PROFESSIONAL GRAPHICS PERFECTED



PART NUMBER:
VCQK5000MAC-PB

Experience the world's most powerful professional graphics on the Apple Mac Pro platform for accelerating professional design, animation and video applications. The new PNY Quadro K5000 taps into the power and efficiency of the NVIDIA Kepler GPU architecture to dramatically accelerate the creative process for professionals.

From small agencies to large media conglomerates, creative pros like you using the Apple Mac Pro want tools that let you bring your vision to life as fast as possible—without sacrificing quality. The PNY Quadro K5000 for Mac gives artists and editors unprecedented power and interactivity. Innovative capabilities for increased throughput and support for up to four displays make it ideal for driving large-scale visualization solutions.

Interact with large, complex scenes in the post-production workflow.

The Quadro K5000's next-generation streaming multiprocessor design offers important architectural changes that can transform your workflow. These include tremendous increases in per-clock throughput of key graphics operations for new levels of performance and power efficiency. Plus the Quadro 5000 features a large, 4 GB frame buffer that lets you work with larger scenes and improve interaction during the creation process.

Easily deploy multi-display desktops for maximum workspace flexibility.

You can now drive up to four displays simultaneously from the two DV-DL and two DisplayPort1.2 connections. DisplayPort1.2 also supports enhanced color depth, higher refresh rates and increased resolutions as high as 3840x2160@60Hz or 4096x2160@ up to 48Hz to enable an expansive workspace and boost productivity.

Trust a solution certified on industry-leading professional applications.

PNY Quadro GPUs are created specifically for professional workstations and power more than 50 professional applications in media and entertainment.

Accelerate performance in Microsoft Windows professional applications.

Experience native Quadro GPU-accelerated 3D graphics performance and features when you're using Apple Boot Camp and running native PC applications.

QUADRO K5000 for Mac- PRODUCT SPECIFICATIONS

CUDA PARALLEL PROCESSING CORES	1536
FRAME BUFFER MEMORY	4 GB GDDR5
MEMORY INTERFACE	256-bit
MEMORY BANDWIDTH	173 GB/s
DISPLAY CONNECTORS	DVH (1) DVI-D (1) DP 1.2 (2) Optional Stereo (1)
SINGLE PRECISION COMPUTE PERFORMANCE	2.1 TERAFLUPS
MAX POWER CONSUMPTION	122 W
GRAPHICS BUS ¹	PCI Express 3.0 x16
FORM FACTOR	110 mm (H) x 265 mm (L) Dual Slot
THERMAL SOLUTION	Active
NVIDIA 3D VISION® / 3D VISION PRO	Support via 3 Pin Mini DIN
QUADRO SYNC	Compatible
HD SDI CAPTURE/OUTPUT	Compatible
GPU DIRECT FOR VIDEO	Compatible



PNY®
PNY Technologies Europe
Contact us at: sales@pny.eu
Tel : +33 (0)5 56 13 75 75

QUADRO K5000 - New NVIDIA Kepler Architecture Features and Benefits for the NVIDIA Quadro K5000

QUAD-DISPLAY SUPPORT	All-new display engine drives up to four displays simultaneously and fully supports the next-generation DisplayPort 1.2 standard capable of resolutions up to 3840x2160. This makes it easy to deploy multiple displays across a desktop, build an expansive digital signage wall, or create a sophisticated stereoscopic 3D CAVE environment.
BINDLESS TEXTURES	Dramatically increases the number of unique textures available to shaders at run-time, enabling vastly more materials and richer texture detail in scenes
NVIDIA SMX	Delivers more processing performance and efficiency through a new, innovative streaming multiprocessor design that allows a greater percentage of space to be applied to processing cores versus control logic
NVIDIA FXAA AND TXAA	Reduces visible aliasing and delivers higher image quality without the performance hit by harnessing the power of the GPU's CUDA cores and new film-style anti-aliasing techniques

Number of synchronized displays/projectors from a single system with NVIDIA® Mosaic technology:

Up to 4	Up to 8	Up to 12	Up to 16
1 GPU	2 GPUs + SLI or 2 GPUs + Quadro Sync	3 GPUs + Quadro Sync	4 GPUs + Quadro Sync

QUADRO K5000 - TECHNICAL SPECIFICATIONS

SUPPORTED PLATFORMS

>> OS X Software Version

3D GRAPHICS ARCHITECTURE

- >> Hardware tessellation engine
- >> NVIDIA® GigaThread™ engine with dual copy engines
- >> Shader Model 5.0 (OpenGL 4.3 and DirectX 11)
- >> Up to 16K x16K texture and render processing
- >> Transparent multisampling and super sampling
- >> 16x angle independent anisotropic filtering
- >> 128-bit floating point performance
- >> 32-bit per-component floating point texture filtering and blending
- >> 64x full scene antialiasing (FSAA)/128x FSAA in SLI Mode
- >> FXAA and TXAA full scene antialiasing
- >> Decode acceleration for MPEG-2, MPEG-4 Part 2 Advanced Simple Profile, H.264, MVC, VC1, DivX (version 3.11 and later), and Flash (10.1 and later)
- >> Dedicated H.264 Encoder³
- >> Blu-ray dual-stream hardware acceleration (supporting HD picture-in-picture playback)

NVIDIA CUDA PARALLEL PROCESSING ARCHITECTURE

- >> SMX architecture (streaming multiprocessor design that delivers greater processing and efficiency)
- >> API support, including:
 - > CUDA C, CUDA C++, DirectCompute 5.0, OpenCL, Java, Python, and Fortran
- >> NVIDIA Parallel DataCache hierarchy (configurable L1 and unified L2 caches)
- >> Error-correction codes (ECC) memory²
- >> 64 KB of RAM (configurable partitioning of shared memory and L1 cache)
- >> Dual Warp Scheduler (schedules and dispatches simultaneously instructions from two independent warps)

ADVANCED DISPLAY FEATURES

- >> 30-bit color (10-bit per each red, green, blue channel)
- >> Support for any combination of four connected displays
- >> Dual DisplayPort 1.2 (supporting resolutions such as 3840x2160 @60 Hz)
- >> Dual-link DVI-I/DVI-D outputs (up to 2560 x1600 @ 60 Hz and 1920x1200 @ 120 Hz)
- >> Internal 400 MHz DAC DVI-I output (analog display up to 2048x1536 @ 85 Hz)
- >> DisplayPort to VGA, DisplayPort to DVI (single-link and dual-link) and DisplayPort to HDMI cables (resolution support based on dongle specifications)
- >> DisplayPort 1.2, HDMI, and HDCP support
- >> 10-bit internal display processing (hardware support for 10-bit scanout for both windowed desktop and full screen, only available on Windows and Linux with Aero disabled)
- >> NVIDIA 3D Vision™ technology, 3D DLP, interleaved, and other 3D stereo format support
- >> Full OpenGL quad buffered stereo support
- >> Underscan/overscan compensation and hardware scaling
- >> NVIDIA nView® multi-display technology
- >> Support for large-scale, ultra-high resolution visualization using the Quadro SVS platform which includes Quadro Mosaic, Quadro Sync and Warp/Blend technologies

DISPLAY PORT AND HDMI DIGITAL AUDIO

- >> Support for the following audio modes:
 - > Dolby Digital (AC3), DTS 5.1, Multichannel (7.1) LPCM, Dolby Digital Plus (DD+), and MPEG-2/ MPEG-4 AAC
- >> Data rates of 44.1 KHz, 48 KHz, 88.2 KHz, 96 KHz, 176 KHz, and 192 KHz
- >> Word sizes of 16 bits, 20 bits, and 24 bits



PNY
PNY Technologies Europe
 Contact us at: sales@pny.eu
 Tel : +33 (0)5 56 13 75 75

PNY PROFESSIONAL RANGE OF PRODUCTS

	 Graphics Solutions by PNY.	QUADRO 400 	QUADRO 410 <i>New!</i> 	QUADRO 600 	QUADRO 2000 	QUADRO 2000D 	QUADRO 4000 	QUADRO K5000 MAC 	QUADRO K5000 <i>New!</i> 	QUADRO 6000
MEMORY		512 Mo DDR3	512 Mo DDR3	1 GB DDR3	1 GB GDDR5	1 GB GDDR5	2 GB GDDR5	4 GB GDDR5	4 GB GDDR5	6 GB GDDR5
MEMORY INTERFACE		64-bit	64-bit	128-bit	128-bit	128-bit	256-bit	256-bit	256-bit	384-bit
MEMORY BANDWIDTH		12.3 GB/s	14 GB/s	25.6 GB/S	41.6 GB/S	41.6 GB/S	89.6 GB/S	173 GB/S	173 GB/S	144 GB/S
CUDA PARALLEL PROCESSING CORES		48	192	96	192	192	256	1536	1536	448
DISPLAY CONNECTORS		Dual-Link DVH (1) DP (1)	Dual-Link DVH (1) DP (1)	DVI-I (1) DP (1)	DVI-I (1) DP (2)	Dual Link DVH (2)	DVI-I (1) DP (2)	DVH (1) DVH-D (1) DP 1.2 (2) Optional Stereo (1)	DVH (1) DVH-D (1) DP 1.2 (2) Optional Stereo (1)	DVI-I (1) DP (2)
INCLUDED ACCESSORIES		DVI to VGA DP to DVI (SL)	DVI to VGA DP to DVI (SL)	DVI to VGA DP to DVI (SL)	DVI to VGA DP to DVI (SL)	DVI to VGA (2)	DVI to VGA DP to DVI (SL) 6-pin power cable	DVI to VGA DP to DVI (SL) 6-pin power cable	DVI to VGA DP to DVI (SL) 6-pin power cable	DVI to VGA DP to DVI (SL) 6-pin power cable
MAXIMUM POWER CONSUMPTION		32 W	38 W	40 W	62 W	62 W	142 W	122 W	122 W	204 W
PHYSICAL DIMENSIONS		69mm (H) x 142mm (L) Single Slot	69 mm (H) x 176 mm (L) Single slot	69mm (H) x 142mm (L) Single Slot	110mm (H) x 178mm (L) Single Slot	110mm (H) x 178mm (L) Single Slot	110 mm (H) x 240 mm (L) Single Slot	110 mm (H) x 260 mm (L) Dual Slot	110 mm (H) x 260 mm (L) Dual Slot	110 mm (H) x 250 mm (L) Dual Slot
3D VISION PRO		Support via USB	Support via USB	Support via USB	Support via USB	Support via USB	3-pin mini DIN	Optional 3-pin mini DIN	Optional 3-pin mini DIN	3-pin mini DIN
GRAPHICS BUS		PCI EXPRESS 2.0 x 16	PCI EXPRESS 2.0 x 16	PCI EXPRESS 2.0 x 16	PCI EXPRESS 2.0 x 16	PCI EXPRESS 2.0 x 16	PCI EXPRESS 2.0 x 16	PCI EXPRESS 3.0 x 16	PCI EXPRESS 3.0 x 16	PCI EXPRESS 2.0 x 16
THERMAL SOLUTION		Active	Active	Active	Active	Active	Active	Active	Active	Active
LOW PROFILE		Yes	Yes	Yes	No	No	No	No	No	No
PART NUMBERS		VCG400-PB	VCG410-PB	VCG600-PB	VCG2000-PB	VCG2000DVI-PB	VCG4000-PB	VCGK5000MAC-PB	VCGK5000-PB	VCG6000-PB
EAN		3536403339579	3536403341299	3536403338916	3536403338893	3536403339494	3536403338404	To be confirmed	3536403338336	3536403338411

	 Graphics Solutions by PNY.	QUADRO G-SYNC 	QUADRO SDI CAPTURE 	QUADRO SDI OUTPUT
ADD-ON CARD FOR		Quadro 5000 Quadro 6000	Quadro 4000 Quadro 5000 Quadro 6000	Quadro 4000 Quadro 5000 Quadro 6000
BUS TYPE		-	PCI-E 2.0 x8	-
CONNECTORS		2x RJ-45 1x BNC	5x BNC	3x BNC 1x DVI-D In
FEATURES		Genlock Frame Lock Swap Lock Synchronization of several workstations, visualisation clusters, caves, videowalls	4x HD-SDI Capture 1x HD-SDI Output 8-Bit, 10-Bit, 12-Bit Ancillary Data SDI capture and postprocessing in realtime. Genlock Preview output	2x HD-SDI Output 8-Bit, 10-Bit, 12-Bit Ancillary Data SDI output and postprocessing in realtime. Genlock

	 GPU Computing by PNY.	TESLA C2075
TOTAL DEDICATED MEMORY		6GB GDDR5
MEMORY SPEED		1.5 GHz
MEMORY INTERFACE		384-bit
# OF CUDA CORES		448
DOUBLE PRECISION FLOATING POINT PERFORMANCE (PEAK)		515 GFlops
SINGLE PRECISION FLOATING POINT PERFORMANCE (PEAK)		1.03 Tflops
POWER CONSUMPTION		225 W
PART NUMBERS		TCSC2075-PB
EAN		3536403340193

PNY Technologies Europe
 Contact us at: sales@pny.eu
 Tel : +33 (0)5 56 13 75 75