

ProArt Display PA148CTV

The Shortcut to Creativity



Key Features



Low Blue Light & Flicker Free



IPS technology is optimized for the finest image quality with 178° wide-viewing-angle



International color standard 100% sRGB / 100% Rec. 709 color space for digital images and video production



Factory pre-calibrated with ASUS advanced gray-scale tracking technology to guarantee the ΔE color difference value is less than 2



10-point Touch

Capacitive 10-point multi-touch capability and Windows 10 compatible



USB Type-C Monitor

USB-C and micro-HDMI ports provide rich connectivity



Control Panel

Virtual Control Panel Integrate Software provides shortcut and customized hotkey to enhance productivity



ASUS Dial

Intuitive ASUS Dial control integrate software and support Microsoft Dial provides shortcut and customized hotkey to enhance productivity



Eye Care

TÜV Rheinland-certified Flicker-free and Low Blue Light technologies to ensure a comfortable viewing experience




Ergo Kick Stand

Ergo Kick Stand design provides intuitive tilt angle adjustment with landscape and portrait view

ASUS

ProArt Display PA148CTV

Spec Sheet

<p>Display</p>	<p>Panel Size : 14-inch (35.56 cm) Wide Screen (16:9) Display Viewing Area (HxV) : 309.37 x 174.02 mm Panel Backlight / Type : IPS True Resolution : 1920 x 1080 Pixel Pitch : 0.160 mm Display Colors : 16.7M Color Saturation : 100% sRGB / 100% Rec. 709 Brightness : 300 cd/m² (typical) Contrast Ratio: 700:1 (typical) ASUS Smart Contrast Ratio (ASCR) : 100,000,000:1 Viewing Angle (CR≥10) : 178° (H)/178° (V) Response Time : 5ms (GTG) Flicker-free : Yes Touch Screen : Yes, Capacitive 10-point multi-touch</p>
<p>Video Feature</p>	<p>Trace Free Technology : Yes ProArt Preset : 9 modes (Standard / sRGB / Rec. 709 / DCI-P3 / Scenery / Reading / Darkroom / User mode1 / User mode2) Color Accuracy : $\Delta E < 2$ ProArt Palette : Yes Gamma Adjustment : Yes (Support Gamma 2.6, 2.4, 2.2, 2.0, and 1.8) Color Adjustment : 6-axis (R, G, B, C, M, Y) Color Temperature Selection : 5 modes QuickFit : Yes (Square / Alignment Grid / Ruler) HDCP support : Yes, 1.4 Adaptive-Sync support: Yes (40~60Hz)</p>
<p>Audio Feature</p>	<p>1W x 2 stereo, RMS</p>
<p>IO ports</p>	<p>Signal Input : USB-C x 2 micro HDMI (v1.4) x 1</p>  <p>micro HDMI USB-C USB-C</p>
<p>Power Consumption</p>	<p>Power On (Typical): <10W Power Saving Mode : <0.5W 100-240V, 50/60Hz</p>
<p>Mechanical Design</p>	<p>Tilt : 15° ~ 75° Pivot : 90° (Clockwise) Tripod Hole: Yes</p>
<p>Dimensions</p>	<p>Phys. Dimension with Stand (WxHxD) : 326.1 x 204.4 x 12.0 mm Box Dimension (WxHxD) : 413 x 342 x 90 mm</p>
<p>Weight</p>	<p>Net Weight (Esti.) : 0.74 kg, Gross Weight (Esti.) : 2.5 kg</p>
<p>Accessories</p>	<p>Power Adaptor, USB-C cable (optional), HDMI to micro HDMI cable (optional), USB-C to USB-A Cable (optional), USB-C to USB-A adaptor (optional), Calibration Report, Quick Start Guide, Warranty Card, Welcome Card</p>
<p>Compliance Standard</p>	<p>Energy Star®, CB, CE Doc., FCC, CCC, BSMI, CU, RVCCI, ErP, CEC, HF, RoHS, WEEE, PC Recycle, WHQL, KCC, KC, e-Standby, TÜV Flicker Free, TÜV Low Blue Light, Calman Verified</p>

* measuring a screen brightness of 200 nits without audio / USB / Card reader connection

**All specifications are subject to change without notice