



MOBILE P3000

PRO PERFORMANCE. ANYTIME. ANYWHERE.

PNY PREVAILPRO P3000 series resets mobile workstation expectations by delivering the power and performance demanded by today's compute and graphics intensive professional applications in a lightweight and ultra-thin form factor. Powered by the NVIDIA Quadro P3000, the PREVAILPRO P3000 offers the ability to interactively work with large and complex models or scenes, drive up to four 4K UHD displays simultaneously and generate photorealistic renders on-the-go - all with unmatched NVIDIA Quadro performance, features and ISV compatibility.

MODEL	BASE	UPGRADED PRO	FEATURES
PART NUMBER	MWS-P3B-ENUSP1-PB	MWS-P3P-ENUSP-PB	
MEMORY	16GB (2 x 8GB) DDR4 2400MHz SODIMM	32GB (2 x 16GB) DDR4 2400MHz SODIMM	KEYBOARD & POINTING DEVICE <ul style="list-style-type: none"> English full size keyboard and numeric keypad with LED backlighting Touchpad with built in TPM fingerprint sensor
PRIMARY STORAGE	128GB M.2 2280 PCIe (Gen. 3 x 4) NVMe SSD	512GB M.2 2280 PCIe (Gen 3 x 4) NVMe SSD	
SECONDARY STORAGE	1TB 2.5" Hard Disk Drive	2TB 2.5" Hard Disk Drive	
DISPLAY	15.6" FHD (1920 x 1080)	15.6" UHD (3840 x 2160)	AUDIO SOUND BLASTER® X-FI® MB5 <ul style="list-style-type: none"> High Definition Audio S/PDIF digital output Built in array microphone Built in dual speakers ANSP™ 3D sound technology on headphone output
ASPECT RATIO	16:9 Panel	16:9 Panel	
PROCESSOR	Intel® Core™ i7-7700HQ processor		I/O PORTS LEFT: <ul style="list-style-type: none"> Security lock slot DC power connector HDMI™ 2.0 with HDCP 2x Mini DisplayPort 1.3 ports 2x Type-C USB 3.1 Gen 2 ports 2x USB 3.1 Gen 1 ports RIGHT: <ul style="list-style-type: none"> 3.5mm 2-in-1 Audio Jack (Microphone S/PDIF optical output) USB 3.1 Gen 1 port 6-in-1 Card Reader RJ-45 LAN port
PROCESSOR SPEED	2.8GHz Base (Boost Up to 3.8GHz)		
PROCESSOR CACHE	6MB Smart Cache		COMMUNICATION <ul style="list-style-type: none"> Built-in 10/100/1000 BASE-T Ethernet Intel® Dual Band Wireless-AC 8265, 2 x 2 AC + BT 4.2 M.2 2230 (Windstorm Peak)
CORE LOGIC	Mobile Intel® HM175 Express Chipset		
MEMORY	Dual channel DDR4, supports up to 2400MHz Two 260 pin SODIMM sockets Expandable memory from 16GB to 32GB		WEB CAM 2.0M FHD video camera POWER SUPPLY Full Range AC adapter, AC in 100~240V, 50~60Hz, DC output 19.5V, 7.7A, 150W BATTERY Embedded 4 cell Li-Polymer battery pack, 55WH; Battery life: 300 minutes (with UMA mode, 55WH battery)
PROFESSIONAL GPU	NVIDIA Quadro Mobile P3000 <ul style="list-style-type: none"> 6GB GDDR5 GPU Memory OpenGL 4.5 DirectX® 12 Vulkan compatible CUDA™, OpenCL, Direct Compute compatible Microsoft Hybrid Graphics Mode <ul style="list-style-type: none"> Supports 4 active displays 		
BIOS			<ul style="list-style-type: none"> 64Mb SPI Flash ROM AMI BIOS
POWER MANAGEMENT			<ul style="list-style-type: none"> ACPI v5.0, Suspend to RAM (S3) Suspend to disk (S4) Soft off (S5) Battery low suspend, Wake on LAN (S5) Wake on USB (S3) Wake on RTC alarm (S4)
LED INDICATORS			Power/Status, Battery, HDD, Airplane Mode, Camera
CERTIFICATES			FCC Class B, CE, cTUVus, TUV, CB, RoHS
ENVIRONMENTAL SPECIFICATIONS			Temperature: <ul style="list-style-type: none"> Operating: 5°C ~ 35°C Non-Operating: -20°C ~ 60°C Relative Humidity: <ul style="list-style-type: none"> Operating: 20% ~ 80% Non-Operating: 10% ~ 90%
OS SUPPORT (OPTIONAL)			Windows® 10 Pro 64-bit
LAPTOP DIMENSIONS			14.96" x 9.8" x 0.73" (380mm x 248mm x 18mm)
WEIGHT			4.8 Lbs. (2.2kg)
CARD READER			6-in-1 Card Reader Supports: <ul style="list-style-type: none"> MMC / RSMHC SD / mini SD / SDHC / SDXC up to UHS-II



THIN AND LIGHT

* Only available on MWS-P3P-ENUSP-PB

Visit www.pny.com/mws-warranty for warranty details.

PNY Technologies, Inc. 100 Jefferson Road, Parsippany, NJ 07054 | Tel 973-515-9700 | Fax 973-560-5590

The PNY logo is a registered trademark of PNY Technologies, Inc. All other trademarks are the property of their respective owners. © 2017 PNY Technologies, Inc. All rights reserved.